


Humidity Sensor Units SYH-2, SYH-2s



Humidity is an important factor in personal comfort and in quality control for materials, machinery etc.

Specifications

Items	SYH-2, SYH-2s
Rated voltage	AC 1V _{rms} (10%)
Rated power	AC 0.22mW
Operating temperature	0~60℃
Operating humidity	20 ~ 95%RH
Standard characteristics	33kΩ (at 25℃, 60%RH)
Storage temperature	-30 ~ 85℃
Storage humidity	Within 95%RH
Humidity accuracy	±5%RH (at 25℃, 60%RH) **1)
Humidity response time	<60 sec. (40 ~ 80%RH)
Hysteresis	±2%RH (40 ~ 80%RH)

**1) possible to ±2%RH by customer requirement

深圳市杰晟兴电子有限公司 JM Components Limited

地址: 深圳市福田区中航路7号鼎诚国际大厦南座2007室


手机: 13662266995 马少良 电话: 0755-83951311

官网: cn-sensor.com

邮编: 518031

传真: 0755-83952401


电邮: jackson@jmcomponents.com





Standard Characteristics

%RH	Spec. (kΩ)
	SYH-2, SYH-2s
20	2890
30	900
40	270
50	81
60	33
70	13
80	5.3
90	2.2
95	1.5

Characteristics Curve




Dimensions (Unit : mm)



SYH-2

.....



SYH-2s